

OCTO CORE INTEL® XEON® PROCESSOR VPX SERVER BLADE

- ▶ Fit for Virtual Machines and HPEC Applications
- Extended Life Cycle and 10-year Silicon Reliability
- Dual 10 Gigabit Ethernet, x8 PCI Express Gen3 Bandwidth
- ▶ 8 Core Xeon[®] Processor D, 16 GB DDR4 with ECC



VX3058 OCTO CORE INTEL® XEON® VPX SERVER BLADE

Featuring the Intel[®] Xeon[®] D processor family (formerly Broadwell-DE), the VX3058 is the first 8-core multiprocessing board of the Kontron 3U VPX ecosystem. The highly integrated 8-core architecture with Dual 10 Gigabit Ethernet, high bandwidth PCI Express 3.0, high speed DDR4 memory, and versatile mezzanine options, is consequently SWaP-C optimized and simply the best choice for high performance embedded computing platforms.

FIT FOR VIRTUAL MACHINES AND HPEC APPLICATIONS

The server class Xeon® D platform is the basis for advanced server applications, built as virtual machines. All capital and operational efficiencies of using isolated workloads which dynamically share common resources will apply. The unchanged application can easily adapt to hardware evolution such as CPU count, memory, I/O availability, or even formfactor. By virtualisation, embedded solutions become a future-proof investment.

VX3058 brings server class applications into the battlefield. Typical applications are:

- 🕨 radar, sonar
- imaging systems
- airborne fighter and UAV radar
- long term programs in harsh environments

LEADING EDGE ARCHITECTURE FOR MULTI-CPU SYSTEMS

VX3058 provides two 10 GBASE-KR ports and 8 lanes Gen3 PCI Express to the backplane. Kontron VxFabric[™] technology provides a TCP/IP protocol over the PCI Express infrastructure towards the application. A 10 Gigabit Ethernet switch and a PCI Express Switch can be complemented with two single star data planes, for 10 GETH and for PCI Express, respectively. A unique API with TCP/IP sockets makes it a powerful, leading edge Multi-CPU computing node architecture.



Kontron's sample turnkey system StarVX implements this architecture, targeting in maximum bandwidth. While computing power has been continuously increasing in the past, and I/O bandwidth did not, the balance of both is back again by Kontron StarVX.



LONG TERM PROGRAMS: HIGH RELIABILITY, LOW TCO

Kontron is providing outstanding elements to increase reliability and to lower Total-Cost-of-Ownership (TCO) for VX3058. Kontron provides a Long Term Supply program service (LTS) for over 15 years. Intel Communications silicon reliability is 10 years. A comprehensive Health Management is optionally available to support easy field maintenance. All this makes the VX3058 the ideal candidate for long term programs.

VERSATILE OPTIONS: XMC, STORAGE, GRAPHICS, M.2, I/O

The M.2 interface can be used for storage or for integration of customized personality modules. A XMC slot and 2-D graphics are additional options. Front-I/O module options are selectable for DVI/HDMI or Ethernet or other interfaces.

More capabilities in 3U space Top M.2 Slot Module

CENTRALIZED HEALTH MANAGEMENT

A shelf manager is optionally available for centralized health management. Moreover, sequenced system power-up and Temperature/Power/Performance management are available. The Power-On Built-in Test (PBIT) option is a comprehensive package for board and system diagnosis.

KONTRON VPX ECO SYSTEM AND VALIDATED SOLUTION

VX3058 boards are compatible with all Kontron 3U VPX and 6U VPX building blocks (payload boards, carriers, switches, backplanes, OS, and drivers) and offer backward compatibility with the previous product generations.

Reduce your time to market by starting with an already complete and validated platform, by use of StarVX turn key systems with off the shelf elements.

PROCESSOR		Intel® Xeon® D-1500 Octo Core™, tuned to 35W, 1.7 GHz (8 execution cores, 16 threads, 12 MB) DDR4 dual channel memory with ECC, 2133 Mbits/s over 144 bits, up to 16 Gbytes Integrated dual 10G Ethernet controller PCIe gen3 x8 ports to VPX and XMC, up to 8 GT/s
ONBOARD CONTROLLER	Integrated Platform Controller Hub Gigabit Ethernet Watchdog System CPLD RTC	 PCI Express* Base Specification, Revision 2.0 support for up to eight ports with transfers up to 5 GT/s Integrated Serial ATA host controllers with independent DMA operation on up to six ports xHCI USB controller provides support for up to 8 USB ports, of which four can be configured as SuperSpeed USB 3.0 ports Two Integrated serial lines One I210 Ethernet controller connected on front panel or VPX backplane (user selection) for 1000BASE-T operation 2nd I210 Ethernet controller connected on VPX backplane for 1000BASE-T operation, and optionally to the front panel (user selection) if the I/O profile option for "2nd RJ-45 Ethernet 1000BASE-T to the front option" is selected. PLD-based, timeout ranging from 2 μs to 510s, IRQ, Reset, dual-stage One CPLD Board controller for power sequencing, reset handling, monitoring, failure detection, VPX I2C communication. Provides configuration/status registers on LPC interface Separated low power RTC with optional onboard battery
MEMORY	System Memory Flash (uEFI BIOS) EEPROM M.2 SSD option	Up to 16 GB dual channel DDR4 SDRAM running at 2133 MT/s, with ECC, soldered 2x16 MB FLASH, with recovery image and uEFI BIOS settings One serial 256 Kbit EEPROM dedicated to system data One serial 256 Kbit EEPROM dedicated to application data M.2 SSD module option: Type M, 22 mm x 42 mm
FRONT INTERFACES 5HP (1")	USB Gigabit Ethernet HDMI (option) Serial LEDs Reset	 1x USB 2.0 port 1x RJ-45 connector: 10/100/1000BASE-T Ethernet Note: This port is configurable from the BIOS to be routed to the VPX rear connector instead HDMI connector as option. This includes a HDMI front-I/O module and a M.2 mezzanine for 2D graphics. Remark: HDMI front I/O and XMC support are exclusive. 1x RJ-11 connector: Two EIA-232 interfaces or one EIA-485 interface from CPU, without hardware flow control 5 LEDs reporting the board CPU health status and activity Reset push button
ONBOARD INTERFACES	Spare PCIe Link M.2 module interface XMC Slot option	 Spare x1 PCle link with clock Top M.2 slot for a 2D graphic module or a SSD module, compatible with a 12mm stacking height XMC slot. M.2 type M standard ping mapping for SSD module or 2D graphic module option Supported module: Type M, 22 mm x 42 mm. One x8 PCle 2 provision for XMC slot option. X8d+X4s VITA 46.9 XMC I/O routing, 8 differential pairs plus 4 single ended pins For XMC slot option, please contact us because of thermal aspects.
VPX INTERFACE	Slot Profiles Rear I/O via PO/ P1/P2 Supervisory Functions	 SLT3-PAY-2F2U-14.2.3 SLT3-PAY-1F1F2U-14.2.4 SLT3-PAY-1F1U-14.2.10 x8 PCle 3.0, non transparent capability, on P1. Configurable as 1 x8, 2 x4, or 4 x2. 2 SATA 6 Gb/s links on P1, 2 additional SATA 6 Gb/s links on P2 2 USB 2.0 and 1 USB 3.0 port on P1, 1 additional USB 2.0 link on P2 2 serial lines (Rx, Tx only) on P2, for R5-232 or R5-422/485 by using dynamic configuration 2 10GBASE-KR or 1000BASE-KX on P1 1 1000BASE-T on P1, 2nd 1000BASE-T on P2 (both front/rear switchable, onboard magnetics) GPIOs on P1: GPIO1, GPIO2/Maskable reset, OpenVPX GDISCRETE1, VBAT, SYSCON. 2x multiplexed GPIO3/4 or SFI 12C on P0 DVI port on P2 as option. This includes a M.2 mezzanine for 2D graphics. Non Maskable RESET NVMRO, Master SMBus and Master/Slave SMBus interfaces for system management. Compatible with Kontron CMB (Monitoring Board), temperature and voltage sensors on the board PCle optional use of common reference clock feature On P0: VS1=12V and 3 3V. AUX: VS2 not used: VS3=5V not used: -12V. AUX for XMC slot option
OS SUPPORT		Linux Fedora 21, ask for: Windows, VxWorks

► VX3058 BLOCK DIAGRAM AND FRONT PANEL



► ENVIRONMENTAL SPECIFICATION

	SA - Standard Commercial (1" single height passive module heat sink, forced air)	RC - Rugged Conduction-Cooled (Depending on processor frequency) Planned, please ask
CONFORMAL COATING	Optional	Standard
AIRFLOW	20 cfm typ. for 35 W TDP NA	
TEMPERATURE	VITA 47-Class AC1 designed to meet (*)	VITA 47-Class CC3, CC4 option designed to meet (*)
COOLING METHOD	Convection	Conduction
OPERATING	0° to +55°C	-40° to +71°C, +85°C option
STORAGE	-45° to +85°C	-45° to +100°C
VIBRATION SINE (OPERATING)	20-500 Hz - 2g	20-2,000 Hz - 5g
RANDOM	VITA 47-Class V1	VITA 47-Class V3
SHOCK (OPERATING)	20g/11 ms Half Sine	40g/11 ms Half Sine
ALTITUDE (OPERATING)	-1,500 to 60,000 ft	-1,500 to 60,000 ft
RELATIVE HUMIDITY	90% without condensation	95% without condensation

^(*) designed to meet: product is ready to pass the required qualification or certification.

► ORDERING INFORMATION

Preferred versions. For ordering information to 16 GB versions or other configurations, please ask your local sales representative.

ARTICLE	ORDER CODE	DESCRIPTION
VX3058	VX30585A881150000	3U single slot 5 HP (1.0") VPX CPU Blade with 8 core Intel® Xeon® D processor, 1.7 GHz, 12 MB, 35W, 8 GB dual-bank DDR4, Base Front-I/O, fully switched x8 PCIe 3, designed to meet Air-Cooled VITA 47 Class AC1 (0°C to +55°C)
VX3058	VX30585A881151000	3U single slot 5 HP (1.0") VPX CPU Blade with 8 core Intel® Xeon® D processor, 1.7 GHz, 12 MB, 35W, 8 GB dual-bank DDR4, Base Front-I/O, additional graphics HDMI front /rear, fully switched x8 PCIe 3, designed to meet Air-Cooled VITA 47 Class AC1 (0°C to +55°C)
VX3058	VX30585A881151000L	3U single slot 5 HP (1.0") VPX CPU Blade with 8 core Intel® Xeon® D processor, 1.7 GHz, 12 MB, 35W, 8 GB dual-bank DDR4; Base front-I/O, additional graphics HDMI front/rear, fully switched x8 PCIe 3, designed to meet Air-Cooled VITA 47 Class AC1 (0°C to +55°C). Specific version with preinstalled Linux Fedora on M.2 SSD Module, to ease product evaluation, not qualified for production

CORPORATE OFFICES	EUROPE, MIDDLE EAST & AFRICA	NORTH AMERICA	ASIA PACIFIC
	Lise-Meitner-Str. 3-5	14118 Stowe Drive	1~2F, 10 Building, No. 8 Liangshuihe 2nd Street,
	86156 Augsburg	Poway, CA 92064-7147	Economical & Technological Development Zone,
	Germany	USA	Beijing, 100176, P.R.China
	Tel.: + 49 821 4086 0	Tel.: + 1 888 294 4558	Tel.: +86 10 63751188
	Fax: + 49 821 4086 111	Fax: + 1 858 677 0898	Fax: +86 10 83682438
	info@kontron.com	info@us.kontron.com	info@kontron.cn

....